

CLASS V UNIVERSAL WELD-ON HITCHES



91523

CLASS V UNIVERSAL WELD-ON HITCH

- Receiver tube opening: 2 ½" x 2 ½"
- Adjustable frame fits many vehicles (side plates do not come pre-welded)
- Fits maximum frame width of 43" and minimum of 18"
- SAE Class V Rated
- Ideal for use with utility boxes
- Adjustable side plates come detached from main body of hitch and must be welded on
- Maximum Gross Trailer Weight (GTW): 16,000 lbs. WC
- Maximum Gross Tongue Weight (TW): 1,600 lbs. WC
- Black powder coat finish
- Weight: 56 lbs.

91533

CLASS V UNIVERSAL WELD-ON HITCH

- Receiver tube opening: 2" x 2"
- Adjustable frame fits many vehicles (side plates do not come pre-welded)
- Fits maximum frame width of 43" and minimum of 18"
- SAE Class V Rated
- Ideal for use with utility boxes
- Adjustable side plates come detached from main body of hitch and must be welded on
- Maximum Gross Trailer Weight (GTW): 16,000 lbs. WC
- Maximum Gross Tongue Weight (TW): 1,600 lbs. WC
- Black powder coat finish
- Weight: 49 lbs.

NOTE: Trailer hitch weight ratings are limited to vehicle manufacturer's stated capacities

ACME Products Company
4347 Clary Boulevard
Kansas City, MO 64130
Ph: 816.921.0444
Ph: 800.821.7576
Fax: 816.921.8451
www.acmehitch.com
steve@acmehitch.com
justin@acmehitch.com